## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

- 1-8. (Canceled)
- 9. (Currently Amended) A mixture, comprising <u>potassium fluoride an alkali</u> metal fluoride or an alkaline-earth metal fluoride or a mixture of both and 2% by weight or less of pyrogenic silicic acid
  - 10. (Canceled)
- 11. (Previously Presented) The mixture of claim 9, characterized in that it contains from 0.2 to 2% by weight of pyrogenic silicic acid, relative to the total weight of the mixture.
- 12. (Previously Presented) The mixture of claim 9, characterized in that it contains from 99 to 99.8% by weight of potassium fluoride and from 0.2 to 1% by weight of pyrogenic silicic acid, each relative to the total amount of the mixture.
- 13. (Currently Amended) A process for the manufacture of the mixture of claim 9, comprising mixing (A) <u>potassium fluoride</u> a dried alkali metal fluoride or a dried alkalineearth metal fluoride or a mixture of both and (B) 2% by weight or less of pyrogenic silicic acid, relative to the total weight of the mixture.
- 14. (Currently Amended) The process of claim 13, wherein the <u>potassium fluoride</u> dried alkali metal fluoride or the dried alkaline earth metal fluoride or the dried mixture of both is obtained by spray drying of a solution, comprising the <u>potassium fluoride</u> alkali metal fluoride or the alkaline earth metal fluoride or the mixture of both.
- 15. (Previously Presented) The process of claim 14, wherein the spray drying is carried out at an inlet temperature in the range of from 300 to 600°C and an outlet temperature of from 130 to 190°C.